


TECHNICAL SPECIFICATIONS



WILSON
CENTER
CAPE FEAR COMMUNITY COLLEGE 



WILMINGTON, NC
01/18/2022



**WILSON
CENTER**
CAPE FEAR COMMUNITY COLLEGE



WILSON CENTER CONTACT LIST

Shane Fernando	Vice President of Advancement and the Arts	910.362.7890	sfernando@cfcc.edu
Nancy Konicki	Executive Assistant	910.362.7207	nkonicki@cfcc.edu
Zach Puer	Senior Managing Director	910.362.7896	zpluer@cfcc.edu
Michael Epting	Technical Director	910.362.7888	mepting@cfcc.edu
Christy Grantham	Director of Ticketing	910.362.7886	cgrantham@cfcc.edu
Brendan Cook	Marketing Manager	910.362.7899	bcook@cfcc.edu

910-362-7999 | 703 North Third Street | Wilmington, NC 28401 | www.capefearstage.com



**WILSON
CENTER**
CAPE FEAR COMMUNITY COLLEGE

Katie Solinski	Communications Manager	910.362.7867	ksolinski@cfcc.edu
Rob Coluccio	Production Manager	910.362.7889	rcoluccio@cfcc.edu
Kathleen Orton	Operations Manager	910.362.7895	korton@cfcc.edu
Andy Cobb	Ticket Central Coordinator	910.362.7850	acobb@cfcc.edu
Annette Freeman	Education & Engagement Coordinator	910.362.7264	afreeman@cfcc.edu
Tammy Daniels	Guest Experience Coordinator	910.362.7891	tdaniels@cfcc.edu
FRONT OF HOUSE STAFF		OFFICE	
Norm Berth	Guest Experience Specialist		
Ruth Slovik	Hospitality Specialist		
TICKET CENTRAL STAFF		OFFICE	
Joey Toler	Ticket Central Agent	910.362.7999	
Cindi Zigler	Ticket Central Agent	910.362.7999	
TECHNICAL STAFF		OFFICE	
Chris Dean	Production Specialist		ckdean549@cfcc.edu
ADDITIONAL SUPPORT		OFFICE	
Guest Services	Volunteers	910.362.7913	
Green Room		910.362.7780	
Wilma Daniels Gallery		910.362.7252	
Fax		910.362.7863	
MAINTENANCE & CUSTODIAL STAFF		OFFICE	
Phil Brown	Maintenance Coordinator	910.362.7353	
Henry Tootoo	Maintenance Coordinator	910.362.7378	




**WILSON
CENTER**
CAPE FEAR COMMUNITY COLLEGE

David Kanoy (LAST CALL)	Director, Maintenance & Custodial Services	910.362.7695
SHERIFF'S OFFICE		OFFICE
Lieutenant Granda (FIRST)	NHC Sherriff's Office	910.798.4138
CAMPUS SECURITY OFFICE		OFFICE
April Harvin	Supervisor, Campus Security	910.362.7825

Performance Hall Seating Capacity


Pit Seating	55
Orchestra	832
Grand Tier	350
Balcony	252
Box Seating	68
Total Capacity	1557





WILSON CENTER

CAPE-FEAR COMMUNITY COLLEGE





**WILSON
CENTER**
CAPE FEAR COMMUNITY COLLEGE

Directions to Fine Arts Center Loading:

From I-40 take Martin Luther King Jr Dr. toward downtown. Continue on to 3rd Street toward downtown. Take a right on Brunswick St. Take the next left on 2nd St. the loading dock will be on the right.

MAP





WILSON
CENTER
CAPE FEAR COMMUNITY COLLEGE

Oversize Vehicle Holding/Overflow Lot:

Advanced arrangements for oversized parking should be made prior to arrival. City ordinances do not allow for tractor trailer or bus parking on the street and there is no secure parking available on site for tractor trailers or multiple busses. Please contact the Technical Director for more information.

2 tractor trailers may remain in the dock after unloading. All other tractor trailers should proceed to either the Overflow Lot or to the Truck Stop.

Directions to the overflow lot. From HFAC Loading Dock: Turn left and take immediate right onto Hanover. Turn left onto Front Street and left onto Red Cross Street. Follow Red Cross and turn left on Tenth Street, then left on Fanning Street—lot will be mid-block on the right. Please park to the right of the awning (14' clearance)

Directions to the Truck Stop: Turn right out of the loading dock and take a right turn onto Brunswick Street. Take a left turn onto 3rd Street. Proceed ½ mile and make a left onto US 421 North. Cross over the Cape Fear River on the Isabella Holmes Bridge. Make a right turn at the first light and the truck stop will be on your right.

BUSES


There is accommodation for (1) tour bus in the loading dock. Passenger side pullouts cannot be utilized if the bus parks nose first in the dock. Driver side pullouts may or may not be deployed depending upon bus configuration. There is (1) 60 amp 3 Phase disconnect in the loading dock. There is (1) fresh water spigot available. There are no dump stations. Buses may not idle while parked in the loading dock. There is a Bus Parking Zone located on the east side of 2nd Street that can accommodate (2) tour buses. There is no shore power for these buses. All vehicles should park in the correct facing direction when parked in the Bus Parking Zone. Buses may not deploy slideouts on the driver's side when parked in the Bus Parking Zone. Buses may deploy passenger side slideouts in between the trees if possible, depending upon bus configuration.



**WILSON
CENTER**
CAPE FEAR COMMUNITY COLLEGE

Map to Overflow Parking

906 Fanning Street





STAGE

Overall Stage dimension	40'-10" deep x 87' 6" wide
Proscenium opening	49'-0" w x 30'-0" h
Plaster Line to upstage wall (Depth)	40'-0"
Plaster Line to last line set	38'-4"
Plaster Line to apron edge	9'-0"
Stage width (excl fly rail)	88'-6"
Center Line to stage left wall	42'-8"
Center Line to stage right wall	45'-10"
Stage Right Wing Dimension	20' wide
Stage Left Wing Dimension	14' wide
Shell Storage	13'-0" deep x 21'-8" wide
Grid height	70'-0"

ORCHESTRA PIT

The orchestra pit is fitted with a Gala Systems Spiralift-Driven Lift. Pit platform is 10'-9" deep at center arcing to 3'-6" at ends x 51'-3" wide. When platform is at pit level, the orchestra pit is 16'-0" deep x 41'-3" wide. Orchestra pit is adjustable to all heights between pit level and stage level.

Pit Level is 8'-6" below Stage Level.

FLOOR CONSTRUCTION

Sprung, dark grey 3/8" Stageboard (HDPE2) surface over two (2) layers of 5/8" plywood on Robbins Bio-Channel Classic sleepers with integral stop blocks (18" centers)

ORCHESTRA SHELL

Wenger DIVA tower and ceiling system. Ten (10) @ 12' wide x 30' tall towers, and three (3) @ 12' deep ceiling panels with integrated lighting. Towers include flip-down reflectors at 18' designed to bring some sound energy back to orchestra. Largest effective usable area within shell is approximately 54' wide x 36' deep (from plaster line).

LOADING DOCK

Covered enclosed loading dock can accommodate two (2) 53' trailers at a time. Loading dock doors cannot be closed unless the trailer is less than 45' long. Trailers back up onto 1 foot high ramps. Center of rear trailer axles should be set to 8' from rear of trailer to avoid striking overhead HVAC ducting. Both docks have a 6' mechanical leveler. Two trucks can be unloaded at once. ICC bar dock locks secure trailers when uncoupled from tractors.

Two (2) roll up doors 10' wide x 10' high lead from loading dock, into a 48' long x 30' wide storage/staging area, to one (1) 16' wide x 20' high roll up door onto the upstage right portion of the stage. Total distance from truck to stage is approximately 30' – 40'.



**WILSON
CENTER**
CAPE-FEAR COMMUNITY COLLEGE

GREEN ROOM/DRESSING ROOMS/WARDROBE ROOM

All support spaces are located at stage level behind stage

- 4-Person: Two (2) 4-person or star dressing rooms with dedicated toilets, sinks and showers.
- 14-Person: Three (3) chorus dressing rooms with dedicated sink. Rooms share two (2) restroom facilities on common corridor, each with 4 sinks, toilets, and shower.
- Green Room: One (1) 470sf green room with small kitchenette located off of dressing room corridor backstage.
- Wardrobe: One (1) 400sf wardrobe / laundry room with two each washers and dryers, and laundry sink.

CHORAL DRESSING ROOM (3)





**WILSON
CENTER**
CAPE FEAR COMMUNITY COLLEGE

STAR DRESSING ROOM (2)





**WILSON
CENTER**
CAPE FEAR COMMUNITY COLLEGE

MIX POSITION

A house mix position is located just behind the cross aisle approximately 65' from the front of the stage. The position is just forward of the balcony. The size of this area is 9'0" deep x 15'-0" wide. Cables from stage pass under house through the plenum to a trap door in the house right rear corner of this area.





RIGGING SYSTEM

Rigging system consists of 49 single purchase counterweight line sets with Schedule 40 1.5” 66’ long battens, each with 4’ batten extensions. Lineset capacity is 1650# each. Arbors are loaded at the Loading Bridge at grid height or Midbridge at 35’ over stage height. Locking rail is located stage left. There is a Midbridge also located stage right 35’ over stage with a 40 position pin rail for cable picks

GRID

Grid is comprised of 1” x 3” C channel laid leg down over I beams with a 3” gap between each channel

Grid Pipe: (20) pieces of 4” Schedule 80 steel pipe, 3’-0” long each.

FRONT OF HOUSE RIGGING POSITIONS

There are (4) 12” I beams accessible through trap doors in the low catwalk subway grate to accommodate front of house truss hanging positions. I beams run parallel to the center line and are located at 7’-0” Stage Left and Stage Right of Center and 21’-0” Stage Left and Stage Right of Center, 42’-0” above the stage floor. Beams are 12’-0” long and begin 4’-0” from the Plaster Line.

Lineset Schedule

SET	POSITION	DESCRIPTION	NOTE
1	1'-0"	66' X 16'	MAIN VALENCE
2	1'-8"	34'6" X 34' 2 PANELS TRACKED	MAIN DRAPE
3	2'-4"		
4	3'-0"	HARD ELECTRIC	1 ST ELECTRIC (2000# CAPACITY)
5	4'-4"		
6	5'-0"	12' X 32'	SL LEG
7	5'-8"	34'6" X 32' 2 PANELS TRACKED	DS BLACK TRAVELER
8	6'-4"	12' X 32'	SR LEG
	7'-0"	SHELL	COUNTERWEIGHT ASSIST
10	8'-4"		
11	9'-8"		



**WILSON
CENTER**
CAPE FEAR COMMUNITY COLLEGE

12	10'-4"	66' X 16'	BORDER
13	11'-0"	12' X 32'	SL LEG
14	11'-8"	12' X 32'	SR LEG
15	12'-4"	SOFT ELECTRIC	2 ND ELECTRIC
16	13'-0"		
17	13'-8"		
18	14'-4"	66' X 16'	BORDER
19	15'-0"	12' X 32'	LEGS
20	15'-8"		
21	16'-4"	SOFT ELECTRIC	WORKLIGHTS/2A ELECTRIC
22	17'-0"		
23	17'-8"	66' X 16'	BORDER
24	18'-4"	SHELL	COUNTERWEIGHT ASSIST
25	19'-8"	34'6" X 32' 2 PANELS TRACKED	MID-STAGE TRAVELER
26	21'-0"		

27	21'-8"	SOFT ELECTRIC	3 RD ELECTRIC
28	22'-4"		
29	23'-0"		
30	23'-8"	66' X 16'	BORDER
31	25'-0"	12' X 32'	LEGS
32	25'-8"		
33	26'-4"		
34	27'-0"		
35	27'-8"		
36	28'-4"	SOFT ELECTRIC	4 TH ELECTRIC
37	29'-0"	66' X 16'	BORDER
38	29'-8"	SHELL	COUNTERWEIGHT ASSIST
39	31'-0"		
40	32'-4"		ELECTRIC 4A
41	33'-0"		
42	33'-8"		
43	34'-4"	66' X 16'	BORDER
44	35'-0"	20' X 32' TRACKED LEGS	UPSTAGE TRAVELER



**WILSON
CENTER**
CAPE-FEAR COMMUNITY COLLEGE

45	35'-8"	SOFT ELECTRIC	CYC ELECTRIC
46	36'-4"		
47	37'-0"		
48	37'-8"		
49	38'-4"	64' X 30' LENO	CYCLORAMA

- 2 - 64' X 30' Black sharktooth scrim are available. Please contact Technical Director for more information.

ELECTRICS / LIGHTING SYSTEM

POWER

Available Lighting Power consists of two (2), 400A Company Switches located at Stage Right to accommodate dimming and power distribution devices for touring applications. Each Company Switch has a connection chamber with shunt-trip access door, and utilizes cam-lock type connectors made up of A phase, B Phase, C Phase, Neutral, Neutral, and Reverse Ground.

INSTALLED PERFORMANCE DIMMING AND CONTROLS

The Performance Dimming and Controls system is comprised four (4) Electronic Theatre Controls (ETC) Sensor3 Dimmer Racks, and one (1) ETC Sensor SineWave rack. In addition, there are (2) 40-circuit Lyntec RPC DMX-Controlled Relay panels are hard-wired to various locations in the theatre.

Circuit distribution is a mix of 6-circuit Veam/Socapex 19-pin connectors and single circuit 20A Stagepin connectors on outlet boxes and connector strips. (408) Performance Circuits are available for 120v dimmed loads. (30) Performance circuits are hard-wired DMX-Controlled relays.

The control system is a network-based system, utilizing ETC Net3/ACN, RDM, and DMX. Portable ACN Gateways may be plugged into any available lighting network port location, allowing conversion of ACN to DMX. The network is capable of powering IEEE 802.3 standard compliant "Power Over Ethernet" Devices (P.O.E.)

CIRCUIT SCHEDULE:

- 1-48: Onstage Wall Boxes
- 49-85: 1st Electric (Hard Electric w/ Connector Strip)
- 86-205: Onstage Gallery Catwalks
- 206-229: Tormentors/Box Booms
- 230-343: FOH Catwalks



WILSON
CENTER
CAPE-FEAR COMMUNITY COLLEGE

- 344-377: Balcony Rails/Under Balcony Ceiling Slot
- 377-384: Orchestra Pit
- 385-408: Orchestra Shell (Sine Wave Dimmers)
- 409-438: Dimmable House Lights
- 439-467: Hard Wired Relays
- 468-Above: Control Switchable and DMX-Dimmable Architectural Lighting

PERFORMANCE LIGHTING FIXTURES AND ACCESSORIES

The Performance Lighting Fixtures and Accessories Package is a hybrid package of both conventional and LED performance fixtures.

PERFORMANCE LIGHTING FIXTURES

Ellipsoidals @750w:

- (7) 5* ETC Source4
- (21) 10* Source4
- (20) 14* Source4
- (75) 19* Source4
- (66) 26* Source4
- (76) 36* Source4
- (40) 50* Source4
- (50) 70* Source4

Fresnels @750w

- (36) ETC Source4 Fresnel

PARs @750w

- (60) ETC Source4 PAR w/ full set lenses

LED and Moving Fixtures:

- (8) D40 Lustr+ ETC/Selador
- (42) D40 Vivid ETC/Selador
- (38) Selador Classic Vivid-R 11" w/ yoke & trunions
- (10) Chauvet Rogue R2 Spot
- (10) Chauvet Rogue R2 Beam
- (21) Rosco Mirocube
- (10) Altman Spectra Cyc 200

Hazer

- - LeMaitre G300 Fog/Haze Machine



WILSON
CENTER
CAPE-FEAR COMMUNITY COLLEGE

Misc. Fixtures:

- (6) The Light Source LED Worklight
- (30) Broadway Music Stand Lights

Followspots @ 2000w

- (2) Strong Super Trouper 2k w/ Tripod Stand

PERFORMANCE LIGHTING ACCESSORIES

- (28) Iris for ETC Source4
- (26) 18" Sidearms
- (8) 10' Booms w/ 50# Bases
- (8) 4-Rung Ladders
- Full complement of Top Hats, Half Hats, Donuts, Color Frames, Template Holders, C-Clamps, and Barndoors.

PERFORMANCE LIGHTING POWER CABLE

Multicable:

- (12) 10' 6-Circ Veam/Socapex 19-pin Multicable Jumper
- (6) 25' 6-Circ Veam/Socapex 19-pin Multicable Jumper
- (12) 50' 6-Circ Veam/Socapex 19-pin Multicable Jumper
- (30) 75' 6-Circ Veam/Socapex 19-pin Multicable Jumper
- (12) 100' 6-Circ Veam/Socapex 19-pin Multicable Jumper
- (36) Fanout - 6-Circ Veam/Socapex 19-pin Multicable to Stagepin
- (30) Breakout 6-Circ Veam/Socapex 19-pin Multicable to Stagepin

Stagepin Cable:

- (36) 20A Stagepin Twofer
- (20) 5' Stagepin Single Circuit Jumper Cable
- (20) 10' Stagepin Single Circuit Jumper Cable
- (20) 25' Stagepin Single Circuit Jumper Cable
- (20) 50' Stagepin Single Circuit Jumper Cable
- (15) 75' Stagepin Single Circuit Jumper Cable
- (15) 100' Stagepin Single Circuit Jumper Cable

PERFORMANCE LIGHTING DATA CABLE AND DMX DEVICES

DMX/Data Devices:

- (1) ETC Gio 2000 Lighting Console w/ 2x20wing and RFR
- (4) Pipe Mount 1x5 DMX OptoIsolator
- (9) 4-Port Net3/CAN/RDM/DMX Gateways
- (1) 1 Lumen Radio Blackbox Transceiver



WILSON
CENTER
CAPE-FEAR COMMUNITY COLLEGE

- (1) SSRC SwitchBrick w/ Lumen Radio Receiver
- Full complement of Network Data & 5-Pin DMX Cables.

GELS AND TEMPLATES

The Cape Fear Community College Humanities and Fine Arts Center does not provide color gels or lighting templates (gobos). We can provide them at cost. Advance notice of at least three weeks is necessary to insure delivery.

SOUND AND COMMUNICATIONS SYSTEMS

POWER

Sound power is an isolated ground / isolated power system with Orange colored convenience outlets throughout the facility. In addition a 200a isolated ground company switch (fed from the same panel) can be found downstage left.

CONSOLES AND SNAKES

1-Yamaha M7CL-48ES with a meter bridge and 3 portable 18x8 stage boxes.
1-Yamaha QL5
1-48X18 Splitter with Transformers
2-20' W4 to FAN (Monitor Split)
2-30' W4 to FAN_FOH Split)
2-75' 16 channel drop snake
Touring consoles may be plugged into house PA at house mix or down left.
All audio snakes must be run through conduit.

DSP

The house DSP takes main speaker feeds and relay feeds, process them and feeds them to house speaker positions, including fill and delay speakers. This signal may also be routed to the relay system and the ALS system.

AMPLIFIERS

House speakers are powered speaker, so there are no amplifiers.

SPEAKERS

The house system consists of:

- JBL Vertec VT4887ADP-DA Powered Compact 3-Way Line Array. 12 boxes per side
- JBL VT4880ADP-DA Powered Fullsize 2-18" Subwoofers. 2 boxes per side.
- A center line array of (4) Renkus Heins CF101LA-52R speakers digitally fed from the DSP
- (16) JBL VP7212MDP Powered 12" 2-way Stage Monitors



- Self-powered 120x 80 monitor speakers: (2) Renkus Heins PN121M/12R digitally fed from the console which may also be fed line level signal.

AUDIO SOURCES AND MICROPHONES

Sources

- CD Player: Dennon DN-C635
- Direct Box: (4) Whirlwind Director
- (2) Rupert Neve 1-Ch Active Instrument DI

Microphones

- (2) Shure Beta 58a
- (4) Shure Sm57
- (9) Shure Sm 58
- (1) Shure Beta 87-C
- (1) Shure Beta 52A
- (5) Shure SM 81
- (2) Shure KSM 32 CG Condenser
- (2) AKG C568B
- (4) Sennheiser E604
- (2) Sennheiser E609
- (2) AKG 414 XLS Matched Pair
- (6) Audio-Technica Hanging Condenser Mic
- (2) DPA 4099 (Bass Clip, Violin Clip, Piano)
- (2) Telefunken M80
- (2) Audio-Technica AT4033 CL Cardioid Condenser
- (4) Shure ULX series Wireless microphones systems
- (6) Countryman E2 headset
- DPA 4061 Omni
- ULX1 Bodypack Transmitter
- (4) ULX2/Beta 58 Handheld
- (8)ULXP4 Receivers

INTERCOM/STAGE MANAGERS CONSOLE

The intercom system is a 4 channel party line system.

- (16) Single channel belt packs and headsets are provided.
There are remote stations at both stage manager's consoles (onstage and one portable for control booth or tech table).
- Wall stations are provided at house management locations.
- (6) Portable cue lights are provided.

ASSISTED LISTENING SYSTEM

Listen 72 mhz FM System with (58) headset receivers and (12) induction loop receivers. This system is equalized and compressed in the DSP and fed the same source as backstage relay signal.



BACKSTAGE RELAY AND PAGING

The backstage relay signal may be fed from a dedicated signal from the house console, a dedicated feed from a touring console, from the Left, center and right channels feeding the main speakers or from dedicated monitor microphones.

This signal is fed via 70v distribution to dressing rooms, backstage areas, the lobby and the control booth.

The stage manager may individually select and page the house, backstage or the lobby via their intercom headset. This page overrides the volume controls in the dressing rooms.

MISCELLANEOUS AUDIO

- 1 BOSE L1 Model 1S System With Tone Match
- (1) PreSonus Studio Live 32 Channel Mixer w/ case
- (1) Air 15S PreSonus 1200W 15" PA Sub
- (2) Air 10 PreSonus 10" 1200W Speaker w/Stand

VIDEO SYSTEMS

A Crestron Digital Media system provides transport of video throughout the theatre. Signals are converted from their native format (including S-Video, RGB Component, Composite, HDMI, DVI, and Displayport) for projection in HDMI. Sources: Blu-Ray / DVD Player, (2) computer interfaces.

VIDEO CAMERAS AND ACCESSORIES

3- Panasonic AG-CX350 4K Camcorders
1-Black-Magic ATEM Television Studio Pro 4K S
1-Atmos 19" On-Set Monitor-Recorder 4KP60 HDR
3-Atmos Ninja V-5" Pro-Res Raw Recorder
3-Small HD 5" Touchscreen Outdoor 800 NIT Moni

PROJECTORS

Barco RLM W14 14,000 Lumen Projector
Barco 0.67 HD/0.73 HB Lens Kit
Barco 4.1-6.9 HD/4.55-7.3 SXGA+ Lens Kit

ORCHESTRA AND DANCE EQUIPMENT

PIANO

- 1 9' STEINWAY Concert Grand Model D



ORCHESTRA CHAIRS AND STANDS

125	Black Wenger Music Chairs
130	Wenger Music Stands
100	Mighty Bright Music Stand Lights
1	Wenger Conductor's Podium & Music Stand

MISCELLANEOUS


10	Rolling Z-Rack
14	6' Folding Tables
4	5' Round Folding Tables
4	Steamers
4	Irons
6	Ironing Boards
5	Black Bar Stools
4	Directors Chairs
9	Bil Jax 4' x 8' Aluminum Risers

DANCE FLOOR

1	50' x 30' Rosco Adagio Dance Floor (6 - 5' x 50' Rolls)
1	Vario Reversible Marley Flooring Black/White (6- 5.25' x 43' Rolls)



WILSON
CENTER
CAPE FEAR COMMUNITY COLLEGE



WILSON
CENTER
CAPE FEAR COMMUNITY COLLEGE

Wilson Center COVID-19 Guidelines

A Message from the Wilson Center Regarding COVID-19...

The health and safety of Cape Fear Community College's faculty, staff, students, and guests is our highest priority.

Cape Fear Community College's policies and protocols for responding to the COVID-19 pandemic were written with the safety of our students, faculty, staff, and visitors to all of our campuses in mind. Our primary goal is to continue the College's vital mission of education and workforce training while providing safe and secure facilities.

This document provides general guidelines to enable Cape Fear Community College to safely operate following guidance from the state of North Carolina, New Hanover County and current restrictions outlined on <https://www.nc.gov/covid-19/staying-ahead-curve>. As the nature of the pandemic continues to change, these guidelines will be updated.

For in-depth safety measures and CFCC campus guidelines, please visit <https://cfcc.edu/coronavirus>.

About COVID-19

The virus is thought to spread mainly from person- to-person, including:

- Between people who are in close contact with one another (within about 6 feet).
- Through respiratory droplets produced when an infected person coughs or sneezes. These droplets can land in the mouths or noses of people who are nearby or possibly be inhaled into the lungs.

It may be possible that a person can get COVID-19 by touching a surface or object that has SARS-CoV-2 on it and then touching their own mouth, nose, or possibly their eyes, but this is not thought to be the primary way the virus spreads.



**WILSON
CENTER**
CAPE-FEAR COMMUNITY COLLEGE

People are thought to be most contagious when they are most symptomatic (i.e., experiencing fever, cough, and/or shortness of breath). Some spread might be possible before people show symptoms; there have been reports of this type of asymptomatic transmission with this new coronavirus, but this is also not thought to be the main way the virus spreads.

Infection with SARS-CoV-2, the virus that causes COVID-19, can cause illness ranging from mild to severe and, in some cases, can be fatal. Symptoms typically include fever, cough, and shortness of breath. Some people infected with the virus have reported experiencing other non-respiratory symptoms. Other people, referred to as *asymptomatic cases*, have experienced no symptoms at all.

According to the CDC, symptoms of COVID-19 may appear in as few as 2 days or as long as 14 days after exposure.

Changes into the way we work

To be able to provide a reasonably safe work environment some engineering controls will be employed until such time that we can resume regular close contact functions again. Some examples of engineering controls for SARS-CoC-2 include:

- Implement exposure reduction solutions
- Change office arrangements to align with social distancing

Safe Work Practices

Safe work practices are types of administrative controls that include procedures for safe and proper work used to reduce the duration, frequency, or intensity of exposure to a hazard. Examples of safe work practices for SARS-CoV-2 include:

- In order to safely welcome back all employees and community members, the Wilson Center will be requiring all employees, interns, volunteers, and contractors who enter the facility, will be required to provide proof of vaccination against COVID-19 to be able to work any shift by October 1st, 2021. Those who cannot show proof of vaccination will be required to provide a negative COVID-19 test (PCR or rapid antigen test, no at-home tests will be accepted) taken within 72 hours of a work shift, no later than 24 hours prior to the start of that shift.
- All staff, crew, volunteers, performers, guests, audience members, and vendors are required to wear a mask, regardless of vaccination status, when in any of the Wilson Center and Cape Fear Community College facilities.
- To protect the health and safety of CFCC employees, students and volunteers, the Venue retains the right to determine and implement any and all safety measures for guests of the performance which they deem necessary in accordance with industry standards and the state of North Carolina guidelines and restrictions. For the latest information regarding guidelines for guests returning to the Center, visit wilsoncentertickets.com/covid-19.
- Venue reserves the right to implement clear social distancing guidelines by use of visual cues, signage, and verbal instructions, and by limiting capacity in all Performance Hall, Lobby, Technical or Backstage areas as needed. A specific plan must be solidified in production meetings to accommodate your group, with the safety of all as the utmost priority.



WILSON
CENTER
CAPE FEAR COMMUNITY COLLEGE

- Any persons permitted backstage must be agreed upon and approved in advance. No other persons are permitted backstage. All approved backstage parties should stay in their designated areas unless absolutely necessary.
- Performer, staff and crew entrances will be one way and limited to only one entrance.. ***Please do not enter the Wilson Center if you are displaying any of the following symptoms:***
 - Coughing
 - Shortness of breath or difficulty breathing
 - Fever
 - Chills
 - Repeated shaking with chills
 - Runny nose or new sinus congestion
 - Muscle pain
 - Sore throat
 - Fatigue
 - New GI symptoms
 - New loss of taste or smell
- Follow the NCDHHS guidance on the 3 Ws:
 - Wear a mask. Care should be taken when putting on/removing a face mask. Wash your hands before and after using a mask. Avoid touching your face and make sure to position it securely over your mouth and nose.
 - Wait 6ft - maintain recommended physical distancing (6 feet or more) from others at all times.
 - Wash your hands often with soap and water for at least 20 seconds. If soap and water are not readily available, please use a hand sanitizer that contains at least 60% alcohol.
- The time between performances and rehearsals will be dictated by the Venue and will be determined in order to allow the Venue to strictly adhere to best practices for disinfecting.
- Rental guests, performers, staff, and volunteers are not permitted to linger in the lobby post-performance. All performers must remain backstage and exit the venue the way they came in. All guests must leave the venue immediately after the conclusion of the performance.
- The protocols listed in this document are non-negotiable.

Personal Protective Equipment (PPE)

While engineering and administrative controls are considered more effective in minimizing exposure to SARS-CoV-2, PPE may also be needed to prevent certain exposures. While correctly using PPE can help prevent some exposures, it should not take the place of other prevention strategies.

Examples of PPE include: gloves, goggles, face shields, face masks, and respiratory protection, when appropriate. During an outbreak of an infectious disease, such as COVID-19, recommendations for PPE specific to occupations or job tasks may change depending on geographic location, updated risk assessments for workers, and information on PPE effectiveness in preventing the spread of COVID-19.